

color+ Series 200 NH

Solvent-based inkjet ink

Color + Series 200 NH Solvent-based inkjet inks.

Color+ Series 200 NH inks have been designed exclusively for the NUR™ Fresco™ wide format printer,

Features

- Solvent-based technology
- Fast drying
- Bright vibrant colours
- Suitable for uncoated materials
- Recommended for both external and internal applications

Ink Properties

Series 200 NH is a high density, highly durable solvent-based pigmented ink for NUR™ Fresco™ printers or similar Piezo drop-on-demand printers utilising XAAR™ head technology. Using the best quality pigments and Sericol Imaging's unique Micro V dispersion technology, Series 200 NH inks provide a wide colour gamut multiplying the number of colours printable whilst simultaneously maximising the outdoor lightfastness for prints with a lasting impact. Color+ Series 200 NH inks have been specifically designed for use with these printers to ensure compatibility and easy change over.

Trichromatic colour range

NH004	Black
NH052	Yellow
NH135	Magenta
NH215	Cyan
QU016	Flushing and cleaning solvent

Available in 5 litre containers

Application Range

Series 200 NH inks are recommended for a wide range of uncoated materials. Main applications include; Display PoP, Poster, Banners, Bus / Taxi advertising and Exhibition Graphics.

Series 200 NH can be used to decorate a wide range of substrates such as:

- Banner Grade PVC
- PVC
- Self-adhesive Vinyl
- Mesh
- Paper

Drying

Series 200 NH inks have been formulated to meet the drying specification of the NUR™ Fresco™ wide format presses using solvent-based inks.

The actual drying speed will depend on a number of factors. These include, ink thickness, substrate choice and the print speed.

THE END USER MUST DETERMINE SUITABILITY OF THIS PRODUCT FOR THE INTENDED USE PRIOR TO PRODUCTION.

Colour and outdoor durability

The highest quality pigments have been chosen for their super-wide colour gamut maximising the range of colours achievable.

Accelerated weathering tests have been carried out in a Xenon Arc weatherometer set to the SAEJ 1960 standard. Under these conditions the accelerated weathering of Series 200 NH inks equate to approximately 24 months outdoor exposure in a temperate climate such as the UK.

Chemical and Abrasion Resistance

Series 200 NH inks have good chemical and abrasion resistance.

Plastics

Certain plastics may be impregnated with lubricants, which may impair adhesion and block resistance even a considerable period of time after printing.

It is normal for Banner Grade PVC to be highly plasticised, which over time migrates to the surface significantly reducing the ink adhesion level. This problem can be overcome by wiping the surface with white spirit before printing.

Head Warranty

Sericol warrant that Series 200 NH inks have been formulated to be compatible with the ink supply system of the NUR™ Fresco™ press and will not cause damage to the print heads providing these inks are used in accordance with NUR's own operating and servicing recommendations and Sericol's ink storage conditions.

If Sericol inks are proven to be the cause of a breakdown, then Sericol will replace the defective parts.

In the case of a claim, any defective part will be subject to analysis in our technical service laboratory to determine the cause and extent of damage due to ink performance.

This warranty is in addition to that set out in Sericol's standard terms and conditions of supply.

SERICOL
More than ink...Solutions.

PRODUCT INFORMATION

The information and recommendations contained in this Product Information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and on condition that users shall make their own tests to satisfy themselves that they will meet fully their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product Information sheet out of date and users are requested to ensure that they follow current recommendations.

SERICOL
More than ink...Solutions.



Sericol Limited Pysons Road Broadstairs Kent CT10 2LE England
Telephone: (01843) 866668 Fax: (01843) 872184

UK Sales - Tel: (01992) 782619 Fax: (01992) 782602
Email: UKsales@Sericol.com

Customer Service Centres - Tel: 0845 084 89 89
Birmingham, Bristol, Gateshead, Glasgow, Leeds,
London, Warrington.

Technical Helpline - Tel: 0845 770 80 70

Export Sales

Pysons Road Broadstairs Kent CT10 2LE England
Tel: +44 (0)1843 866668 Fax: +44 (0)1843 872122
Email: Exportsales@Sericol.com

www.sericol.com

PRINTED IN ENGLAND 1856/N4